

## Feeds



Lightweight & durable



Customizable options



Built to perform



As the premier provider of drilling solutions, Komatsu Mining's extensive experience performing conversions means a seamless transition, **regardless of the drill manufacturer.**

Telescopic and Fixed Drilling feeds are available for conversion. Feed components are lightweight, durable, cost-effective, and optimized for performance.

### TELESCOPIC FEEDS

Can be custom made for a variety of collapsible configurations:

- 8/12 ft
- 8/14 ft
- 10/16 ft

Can be set up with several options:

- Hydraulic centralizer
- Heavy-duty feed cylinder for probe drilling

### STANDARD FIXED FEED FEATURES

Aluminum lightweight components including:

- Feed beam & bolt-on foot adapter
- Cradle assemblies
- Centralizer components
- Quick-release feed cable system
- Same length of feed cables

### OPTIONAL FIXED FEED FEATURES

- Auto-return/ impulse cylinder systems
- Hydraulic centralizer
- Multiple drill steel changers
- Heavy-duty probe feed cylinder
- Heavy-duty feed cables
- Lightweight, durable, cost-effective urethane parts including:
  - Hose drum
  - Bulkhead assembly
  - Hose guide assembly
  - Centralizer assembly

**Unit specifications**

Fixed feed length options	8', 10', 12', 14', 16', 18'
Telescopic feed length options	8'/12', 8'/14', 10'/16'

**Drifter options**

Optional drifters	HC25, HC28, HC50, HC95, HC110
-------------------	-------------------------------

Feed options	Standard	Option
Fixed centralizer	X	
Hydraulic centralizer		X
Drill steel handler		X
Heavy-duty probe drilling cylinder		X

**Fixed feeds**

Drifter option	Drill steel length (ft/mm)	Hole depth (mm)	Overall length (mm)
HC50/HC95	10/3048	2768	4673
HC50/HC95	12/3658	3378	5283
HC50/HC95	14/4267	3988	5893
HC50/HC95	16/4877	4598	6503
HC110	12/3658	3378	5459
HC110	14/4267	3988	6069
HC110	16/4877	4598	6679
HC110	18/5486	5208	7289

\*Weight is for standard fixed feed with fixed centralizer option, no drifter, no hoses

**Telescopic feeds**

Drifter option	Drill steel length (ft/mm)	Hole depth (mm)	Overall length (mm)
HC50/HC95	8/2439	3378	4017/5237
HC50/HC95	8/2439	3988	4017/5846
HC50/HC95	10/3048	4598	4627/6456
HC110	8/2439	3378	4197/5417
HC110	8/2439	3988	4197/6026
HC110	10/3048	4598	4807/6636

\*Weight is for standard fixed feed with fixed centralizer option, no drifter, no hoses

**Komatsu: Revolutionizing the mining industry for a sustainable future**

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu, Joy, Montabert, P&H, Timberock and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu Mining Corp., or their respective owners or licensees.

© 2019 Komatsu Mining Corp. All rights reserved.

EN-DF01-0719-V1

mining.komatsu